

#620 SYNQUENCH FRH FLUID ISO 68

Schaeffer Manufacturing's #620 Synquench FRH ISO 68 fluid is a polyol ester base fire resistant hydraulic fluid that is recommended for those hydraulic applications where potential fire hazards exist.

Synquench FRH Fluid ISO 68 is blended from the highest quality polyol ester base fluids available. These polyol ester base fluids provide Synquench FRH Fluid with the following advantages:

1. Excellent Lubricity Characteristics.
2. Excellent Viscosity-Temperature Relationship. These polyol esters provide the Synquench FRH Fluid with a viscosity index greater than 200. This extremely high viscosity index allows #620 Synquench FRH Fluid to exhibit little change in viscosity with changes in temperature. This excellent viscosity-temperature properly results in maximum hydraulic efficiency and minimum difficulty in operating over a wide range of temperatures.
3. Low Acid Numbers and Hydroxyl Values. These low acid numbers and hydroxyl values provide excellent resistance to the formation of varnish and lacquer deposits, especially under high temperature conditions. This also results in increased fluid stability and extended service life.
4. High Flash Point Autoignition Temperatures. This results in a fluid that is more difficult to ignite and therefore, safer to use than petroleum oils.
5. Excellent Low Temperature Properties.
6. Excellent Resistance to Thermal Degradation.

Blended into these polyol ester base fluids is a highly specialized additive package. This additive package provides #620 Synquench FRH Fluid ISO 68 with exceptional anti-wear, rust and oxidation inhibiting, corrosion inhibiting and demulsibility properties.

#620 Synquench FRH ISO 68 is compatible with all ferrous and non-ferrous metals and their alloys. #620 Synquench FRH Fluid ISO 68 is also compatible with the following elastomers normally used with base oil hydraulic fluid:

| <u>Elastomers</u> | <u>Compatibility</u> |
|------------------------------------|------------------------------------|
| Fluoro-elastomers (Vitron, Teflon) | Satisfactory |
| Nitrile Buna N | Satisfactory |
| Polyurethane | Satisfactory |
| Nylon | Satisfactory |
| Silicon Rubber | Satisfactory |
| Butyl | Satisfactory but with reduced life |
| Ethylene Propylene | Satisfactory but with reduced life |
| EPR | Satisfactory but with reduced life |
| Neoprene | Satisfactory but with reduced life |
| Low Nitrile Buna N | Satisfactory but with reduced life |

Continued on Next Page

TD-620 (Rev. 5/96)

Schaeffer Manufacturing's #620 Synquench FRH Fluid ISO 68 has specific gravity that is less than water. This aspect, in addition to its excellent demulsibility properties, allows it to be removed from ponds and collection tanks by standard skimming techniques. Further, #620 Synquench FRH Fluid ISO 68 does not contain phenols, phenol derivatives, or any other materials that are considered to be hazardous by the EPA.

#620 Synquench FRH Fluid ISO 68 is relatively non-toxic and does not require any industrial handling or health hazard precautions. However, it is suggested that standard industrial hygiene be practiced. Precautions can also be taken by the use of protective goggles and gloves.

#620 Synquench FRH Fluid ISO 68, like any other synthetic fluid, under the proper circumstances, will burn. However, unlike some synthetic base fluids when burned, #620 Synquench FRH Fluid ISO 68 does not evolve large volumes of dense and noxious smoke and fumes.

#620 Synquench FRH Fluid ISO 68 meets and exceeds Denison HF-5, Sperry Vickers and Factory Mutual's Class II less hazardous fluid rating.

Installation

To Convert from Other Polyol Ester Fluids, Phosphate Esters or Oil-Synthetic Blends:

#620 Synquench FRH Fluids are compatible and miscible with polyol esters, phosphate esters and oil-synthetic blends, as long as the used fluids are in condition and contain no water. Simply add #620 Synquench FRH Fluid to the system, or to completely convert, drain the oil fluid (it can be used elsewhere) and recharge with #620 Synquench FRH Fluid. Flushing is not necessary.

To Convert from Water Containing Fluids:

Water containing fluids such as water glycols, inert emulsions and thickened high water content fluids must be thoroughly drained and the system flushed with #620 Synquench FRH Fluid. For optimum performance, the operational #620 Synquench FRH Fluid should have a water content less than 1%.

To Convert from Petroleum Oil-Based Fluids:

Completely drain and recharge system with #620 Synquench FRH Fluid. However, to preserve the highest degree of fire resistance, petroleum oil residual should be less than 5%. Depending upon the system design, this may require a flush with #620 Synquench FRH Fluid following the drain. In all conversions, consideration should be given to the use of proper seals and hoses. This is also an appropriate time for the cleaning and/or replacement of suction strainers and filter elements to ensure trouble free operation after the changeover.

Schaeffer Manufacturing's technical service engineers are available to assist you and arrange for the monitoring of the new fluid's condition following the conversion.

Typical Properties

| | |
|--|--------------|
| ISO Grade | 68 |
| Specific Gravity 60°F | .91 |
| Viscosity 40°C cSt (ASTM D-445) | 63.5-75 |
| Viscosity 100°C cSt (ASTM D-445) | 12.51-14.32 |
| Viscosity Index (ASTM D-2270) | 200 |
| Pour Point °F/°C (ASTM D-97) | -30°/-34.44° |
| Flash Point °F/°C (ASTM D-92) | 560°/293.3° |
| Fire Point °F/°C (ASTM D-92) | 640°/337.78° |
| Autoignition Temperature °F/°C | 900°/482.22° |
| ISO Cleanliness Level | 17/15 |
| Total Acid Number (ASTM D-974) | 1-1.5 |
| Rust Test (ASTM D-664) | |
| Procedure A (Distilled Water) | Pass |
| Procedure B (Salt Water) | Pass |
| Copper Strip Corrosion Test (ASTM D-130) | |
| 3 Hours | 1a |
| Four Ball Wear Test (ASTM D-2266) | |
| (1 hr/40kg/130°F) | |
| Wear Scar Diameter, mm | .45 |
| Demulsibility (ASTM D-1401) | |
| Oil/Water/Emulsion | 40-40-0 |
| Time, min. | 20 |
| Foaming Tendency (ASTM D-892) | Pass |
| Pump Wear Test (ASTM D-2882) | |
| Weight Loss, Ring and Vane Combined, mg. | 10-15 |

#620 Synquench FRH Fluid ISO 68 is available in bulk, 55 gallon drums and 5 gallon pails.